

Printing date 14.06.2018

Version number 3

Revision: 02.04.2018

SECTION 1: Identification of the substance/mixture and of the company/ undertaking 1.1 Product identifier Trade name: ROC Leatherglue

- /ROC Læderlim
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Product category PC1 Adhesives, sealants
- · Application of the substance / the mixture Glue for leather, fabric & rubber.
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: ROC Danmark ApS Thorslundsvej 7 5000 Odense C +45 87 41 66 11 www.roc.dk
- · Informing department: Regulatory Department
- 1.4 Emergency telephone number:
- NCEC emergency service +44 (0) 1235 239 670 (24 hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008
- Flam. Liq. 2H225 Highly flammable liquid and vapour.Skin Irrit. 2H315 Causes skin irritation.STOT SE 3H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

 Hazard-determining components of labelling: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Hydrocarbons, C6 isoalkanes, <5% n-hexane
 Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
 Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 Use explosion-proof electrical/ventilating/lighting equipment.

(Contd. on page 2)

GB

Printing date 14.06.2018

Version number 3

Revision: 02.04.2018

Trade name: ROC Leatherglue/ ROC Læderlim

	(Contd. of page	∋1)
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P303+P361+P353	FON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin w	ith
	water/shower.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national/internation	nal
2.3 Other hazard	regulations.	

2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• **Description:** Adhesive.

Natural rubber

Dangerous components:

 Dangerous components: 		
EC number: 927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (*)	50-100%
Reg.nr.: 01-2119475515-33	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	
	Hydrocarbons, C6, isoalkanes, <5% n-hexane (*)	25-50%
Reg.nr.: 01-2119484651-34	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	
Additional information Ear	the wording of the listed bezord phrases refer to section 16	

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information
 No special measures required.
 Instantly remove any clothing soiled by the product.
- Take affected persons into the open air.
- After inhalation Supply fresh air; consult doctor in case of symptoms.
- After skin contact Instantly wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
- After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

Instantly call for doctor.

Do not induce vomiting; instantly call for medical help.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 3)

GP

Printing date 14.06.2018

Version number 3

Revision: 02.04.2018

Trade name: ROC Leatherglue/

ROC Læderlim

(Contd. of page 2)

5 1 Extinguishing modia	
5.1 Extinguishing media Suitable extinguishing ager	nts
Use fire fighting measures the	
Water haze	
Foam	
Fire-extinguishing powder	
Carbon dioxide	
	ble extinguishing agents Water with a full water jet.
	from the substance or mixture ossible during heating or in case of fire.
Can be released in case of fir	
Carbon monoxide and carbon	
5.3 Advice for firefighters	
Protective equipment: Do no	ot inhale explosion gases or combustion gases.
Additional information	
Cool endangered containers	
	ting water separately. It must not enter drains. ntaminated fire fighting water in accordance with official regulations.
-	
SECTION 6: Accidenta	
SECTION 0. Accidental	release measures
6.1 Personal precautions, p	rotective equipment and emergency procedures
	inst the effects of fumes/dust/aerosol.
	Keep unprotected persons away.
Ensure adequate ventilation	
Keep away from ignition sourd Wear protective clothing.	Ces
6.2 Environmental precautio	ons:
	e system, surface or ground water.
	in case product reaches water or sewage system.
	or containment and cleaning up:
Inform respective authorities i 6.3 Methods and material fo	
Inform respective authorities i 6.3 Methods and material for Dispose of contaminated mat	erial as waste according to item 13.
Inform respective authorities i 6.3 Methods and material for Dispose of contaminated mate Absorb with liquid-binding ma	terial as waste according to item 13. Iterial (sand, diatomite, acid binders, universal binders, sawdust).
Inform respective authorities in 6.3 Methods and material fo Dispose of contaminated mate Absorb with liquid-binding mang Ensure adequate ventilation.	terial (sand, diatomite, acid binders, universal binders, sawdust).
Inform respective authorities in 6.3 Methods and material fo Dispose of contaminated mate Absorb with liquid-binding ma Ensure adequate ventilation. Do not flush with water or aqu	iterial (sand, diatomite, acid binders, universal binders, sawdust). Jeous cleansing agents
Inform respective authorities in 6.3 Methods and material fo Dispose of contaminated mate Absorb with liquid-binding ma Ensure adequate ventilation. Do not flush with water or aqu Send for recovery or disposal	nterial (sand, diatomite, acid binders, universal binders, sawdust). Jeous cleansing agents I in suitable containers.
Inform respective authorities in 6.3 Methods and material fo Dispose of contaminated mate Absorb with liquid-binding ma Ensure adequate ventilation. Do not flush with water or aqu Send for recovery or disposal Do not use tools that can cau	nterial (sand, diatomite, acid binders, universal binders, sawdust). Jeous cleansing agents I in suitable containers. Ise ignition.
Inform respective authorities in 6.3 Methods and material for Dispose of contaminated mate Absorb with liquid-binding ma Ensure adequate ventilation. Do not flush with water or aqu Send for recovery or disposal Do not use tools that can caus 6.4 Reference to other secti	nterial (sand, diatomite, acid binders, universal binders, sawdust). Jeous cleansing agents I in suitable containers. Ise ignition. ions
Inform respective authorities in 6.3 Methods and material for Dispose of contaminated mate Absorb with liquid-binding ma Ensure adequate ventilation. Do not flush with water or aqu Send for recovery or disposal Do not use tools that can cause 6.4 Reference to other section See Section 7 for information	nterial (sand, diatomite, acid binders, universal binders, sawdust). Jeous cleansing agents I in suitable containers. I is e ignition. ions on safe handling on personal protection equipment.

· 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed containers. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Take note of emission threshold.

(Contd. on page 4)

GB

Printing date 14.06.2018

Storage

Version number 3

Revision: 02.04.2018

(Contd. of page 3)

Trade name: ROC Leatherglue/ **ROC Læderlim**

> Use solvent-proof equipment. Keep out of the reach of children.

Protect against electrostatic charges.

Keep container tightly sealed. Protect from heat and direct sunlight.

· 8.1 Control parameters

· 8.2 Exposure controls

monitored at the workplace.

· Personal protective equipment

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Protective gloves.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke. Highly volatile, flammable constituents are released during processing. Fumes can combine with air to form an explosive mixture. Flammable mixtures may be formed in empty containers. 7.2 Conditions for safe storage, including any incompatibilities · Requirements to be met by storerooms and containers: Provide solvent resistant, sealed floor. Information about storage in one common storage facility: Store away from foodstuffs. · Further information about storage conditions: Store in cool, dry conditions in original sealed container · 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection · Additional information about design of technical systems: No further data; see item 7. · Components with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be · Additional information: The lists that were valid during the compilation were used as basis. · General protective and hygienic measures The usual precautionary measures should be adhered to general rules for handling chemicals. Keep away from foodstuffs, beverages and food. Take off immediately all contaminated clothing Wash hands during breaks and at the end of the work. · Breathing equipment: Use breathing protection in case of insufficient ventilation. · Recommended filter device for short term use: Combination filter A-P2

Solvent resistant gloves

· Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 5)

Printing date 14.06.2018

Version number 3

Revision: 02.04.2018

Trade name: ROC Leatherglue/ **ROC Læderlim**

(Contd. of page 4) substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Butyl rubber, BR

- · Penetration time of glove material The information is based on literature data and information of glove manufacturers. Value for the permeation: Level ≤ 4
- As protection from splashes gloves made of the following materials are suitable: Natural rubber, NR
- · Not suitable are gloves made of the following materials: PVC gloves
- · Eye protection:



Tightly sealed safety glasses.

· Body protection:

Heat-resistant protective clothing Protective work clothing.

SECTION 9: Physical and chemical properties

General Information	
Appearance:	
Form:	Fluid
Colour:	Beige
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Not determined
Initial boiling point and boiling range	: 63 °C
Flash point:	-26 °C (DIN 53213)
Inflammability (solid, gaseous)	Not applicable.
Decomposition temperature:	Not determined.
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
Critical values for explosion:	
Lower:	0.9 Vol %
Upper:	8.0 Vol %
Vapour pressure:	Not determined.
Density at 20 °C	0.700 +/- 0.010 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

Printing date 14.06.2018

Version number 3

Revision: 02.04.2018

Trade name: ROC Leatherglue/ ROC Læderlim

	(Contd. of page 5
Not miscible or difficult to mix	
Not determined.	
7 000 - 8 500 mPas (Brookfield) Not determined.	
86.5-89.5 %	
10.5-13.5 % (ISO 3251) No further relevant information available.	
	Not determined. 7 000 - 8 500 mPas (Brookfield) Not determined. 86.5-89.5 % 10.5-13.5 % (ISO 3251)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with alcohols, amines, aqueous acids and alkalis Develops readily flammable gases / fumes
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Possible in traces.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

110-54-3	n-hexane	
Oral	LD50	28710 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)
110-82-7	cyclohexa	ane
Oral	LD50	12705 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)
Inhalative	LC50/4h	26 mg/l (rat)
· Primary i	rritant eff	ect:
· Skin corr	osion/irri	tation
Causes sl	kin irritatio	n.
· Serious e	ye damag	ge/irritation Based on available data, the classification criteria are not met.
· Respirato	ory or skii	n sensitisation Based on available data, the classification criteria are not met.
. CMR offo	rts (rarci	inogenity, mutagenicity and toxicity for reproduction)

• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB

Printing date 14.06.2018

Version number 3

Revision: 02.04.2018

(Contd. of page 6)

Trade name: ROC Leatherglue/ ROC Læderlim

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

110-54-3 n-hexane

IC50/96h 1079 mg/l (Chlorella vulgaris)

LC50/24h 4 mg/l (Carassius auratus)

EC50/48h 2.1 mg/l (Daphnia magna)

110-82-7 cyclohexane

LC50/96h 34 mg/l (Lepomis macrochirus)

IC50/72h > 500 mg/l (Desmodesmus subspicatus)

EC50/48h 3.78 mg/l (Daphnia magna)

· 12.2 Persistence and degradability

110-82-7 cyclohexane

Bio.Abbaubark./28 d 6 % (-)

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow product to reach ground water, water bodies or sewage system. Also poisonous for fish and plankton in water bodies.

Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated under adherence to official regulations.

• European waste catalogue 08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 04 00 wastes from MFSU of adhesives and sealants (including waterproofing products)

(Contd. on page 8)

GB

Printing date 14.06.2018

Version number 3

Revision: 02.04.2018

Trade name: ROC Leatherglue/ ROC Læderlim

> (Contd. of page 7) 08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
· ADR, IMDG, IATA	UN1133
14.2 UN proper shipping name	
ADR	1133 ADHESIVES, ENVIRONMENTALLY
IMDG	HAZARDOUS ADHESIVES (Naphtha (petroleum),
	hydrodesulfurized light dearomatized (*), Naphtha
	(petroleum), hydrotreated light (*)), MARINE
ΙΑΤΑ	POLLUTANT ADHESIVES
	ADHESIVES
• 14.3 Transport hazard class(es)	
ADR, IMDG	
Class	3 Flammable liquids.
Label	3
· IATA	
· Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	111
- 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrodesulfurize
	light dearomatized (*), Naphtha (petroleum), hydrodesullunze
	hydrotreated light (*)
Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Kemler Number:	33
· EMS Number: · Stowage Category	F-E,S-D A

Printing date 14.06.2018

Version number 3

Revision: 02.04.2018

Trade name: ROC Leatherglue/ ROC Læderlim

14.7 Transport in bulk according to Ann Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 n
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 n
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations
- · Technical instructions (air):

ClassShare in %NK50-100

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· VOC (EU) % 88.10 %

· VOC (EÚ) 616.7 g/l

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

- · Department issuing data specification sheet: Environment, Health & Safety Department
- Contact: EU-MSDS@hbfuller.com

(Contd. on page 10)

GB

Printing date 14.06.2018

Version number 3

Revision: 02.04.2018

Trade name: ROC Leatherglue/ ROC Læderlim

	(Contd. of page
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin Concerning the International Transport of Dangerous Goods by Rail)	de fer (Regulations
ICAO: International Civil Aviation Organisation	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agre	eement concerning the
International Carriage of Dangerous Goods by Road)	-
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Lig. 2: Flammable liquids – Category 2	
Skin Irrit. 2: Skin corrosion/irritation – Čategory 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2	
* Data compared to the previous version altered.	
Data compared to the previous version altered.	